



## INFORMATION SHEET FOR AIR CONDITIONERS, EXCEPT DOUBLE DUCTS AND SINGLE DUCTS<sup>(5)</sup>

AS by Commission Communication in the framework of ecodesign requirements for air conditioners and comfort fans (EU Regulation no. 206/2012 ) and of energy labelling of air conditioners - (EU Regulation no. 626/2011).

### MODEL : X3I ECO PLUS 70 SH / X3I ECO PLUS 70 HL WF

Function to which information applies				If information applies to heating: heating season to which information relates.			
Cooling		Y		Heating (Average)(-10°C)		Y	
Heating		Y		Heating (Warmer)(+2°C)		Y	
				Heating (Colder)(-22°C)		Y	
Item	symbol	value	unit	Item	symbol	value	unit
<b>Design load</b>				<b>Seasonal efficiency</b>			
Cooling	Pdesignc	7,0	kW	Cooling	SEER	6,5	-
Heating (Average)(-10°C)	Pdesignh	6,4	kW	Heating (Average)(-10°C)	SCOP (A)	4,0	-
Heating (Warmer)(+2°C)	Pdesignh	6,9	kW	Heating (Warmer)(+2°C)	SCOP (W)	5,1	-
Heating (Colder)(-22°C)	Pdesignh	6,3	kW	Heating (Colder)(-22°C)	SCOP (C)	3,3	-
<b>Declared capacity (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj</b>				<b>Declared Energy efficiency ratio (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj</b>			
Tj = 35°C	Pdc	7,03	kW	Tj = 35°C	EERd	3,60	-
Tj = 30°C	Pdc	5,09	kW	Tj = 30°C	EERd	5,20	-
Tj = 25°C	Pdc	3,21	kW	Tj = 25°C	EERd	7,34	-
Tj = 20°C	Pdc	2,68	kW	Tj = 20°C	EERd	11,76	-
<b>Declared capacity (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj</b>				<b>Declared Coefficient of Performance (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj = -7°C	Pdh	5,79	kW	Tj = -7°C	COPd	2,62	-
Tj = 2°C	Pdh	3,61	kW	Tj = 2°C	COPd	4,21	-
Tj = 7°C	Pdh	2,21	kW	Tj = 7°C	COPd	4,93	-
Tj = 12°C	Pdh	1,90	kW	Tj = 12°C	COPd	5,80	-
Tj = bivalent temperature	Pdh	5,79	kW	Tj = bivalent temperature	COPd	2,62	-
Tj = operating limit temperature	Pdh	6,24	kW	Tj = operating limit temperature	COPd	1,79	-
<b>Declared capacity (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj</b>				<b>Declared Coefficient of Performance (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj = 2°C	Pdh	7,23	kW	Tj = 2°C	COPd	2,64	-
Tj = 7°C	Pdh	4,45	kW	Tj = 7°C	COPd	4,88	-
Tj = 12°C	Pdh	2,02	kW	Tj = 12°C	COPd	5,85	-
Tj = bivalent temperature	Pdh	7,23	kW	Tj = bivalent temperature	COPd	2,64	-
Tj = operating limit temperature	Pdh	7,23	kW	Tj = operating limit temperature	COPd	2,64	-
<b>Declared capacity (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj</b>				<b>Declared Coefficient of Performance (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj</b>			
Tj = -7°C	Pdh	3,87	kW	Tj = -7°C	COPd	2,97	-
Tj = 2°C	Pdh	2,33	kW	Tj = 2°C	COPd	4,15	-
Tj = 7°C	Pdh	1,73	kW	Tj = 7°C	COPd	4,66	-
Tj = 12°C	Pdh	1,82	kW	Tj = 12°C	COPd	5,61	-
Tj = bivalent temperature	Pdh	6,56	kW	Tj = bivalent temperature	COPd	1,84	-
Tj = operating limit temperature	Pdh	5,99	kW	Tj = operating limit temperature	COPd	1,79	-
Tj = -15°C	Pdh	-	kW	Tj = -15°C	COPd	-	-
<b>Bivalent temperature</b>				<b>Operating limit temperature</b>			
Heating (Average)	Tbiv	-7	°C	Heating (Average)	Tol	-7	°C
Heating (Warmer)	Tbiv	2	°C	Heating (Warmer)	Tol	2	°C
Heating (Colder)	Tbiv	-15	°C	Heating (Colder)	Tol	-20	°C
<b>Power consumption of cycling</b>				<b>Efficiency of cycling</b>			
Cooling	Pcycc	nd	kW	Cooling	EERcyc	na	-
Heating	Pcyh	nd	kW	Heating	COPcyc	na	-
Degradation coefficient cooling(**)	Cdc	0,25	-	Degradation coefficient heating(**)	Cdh	0,25	-
<b>Electric power input in power modes other than "active mode"</b>				<b>Seasonal electricity consumption</b>			
Off mode	P <sub>OFF</sub>	0,000547	W	Cooling	Q <sub>CE</sub>	377	kWh/a
Standby mode	P <sub>SB</sub>	0,000547	W	Heating (Average)(-10°C)	Q <sub>HE/A</sub>	2240	kWh/a
Thermostat-off mode	P <sub>TO</sub>	0,00235/0,0048	W	Heating (Warmer)(+2°C)	Q <sub>HE/W</sub>	1894	kWh/a
Crankcase heater mode	P <sub>CK</sub>	0	W	Heating (Colder)(-22°C)	Q <sub>HE/C</sub>	4009	kWh/a
<b>Capacity control type</b>				<b>Other items</b>			
Fixed		N		Sound power level (indoor/outdoor)	L <sub>WA</sub>	63/67	dB(A)
Staged		N		Refrigerant type		R32	
Variable		Y		Global warming potential	GWP	675	KgCO <sub>2</sub> eq.
				Rated air flow (indoor/outdoor)		1250/3200	m <sup>3</sup> /h
For more detailed information				<b>ARGOCLIMA SPA - Via A. Varo,35 - Alfianello (BS) - ITALY - www.argoclima.com</b>			

(5) For multisplit appliances, data shall be provided at a Capacity ratio of 1.

(\*\*) If default Cd= 0,25 is chosen, then results from cycling tests are not required. Otherwise either the heating or cooling cycling test value is required



## Product Fiche

**Model:** X3I ECO PLUS 70 SH / X3I ECO PLUS 70 HL WF

**Manufacturer :** ARGOCLIMA SPA - via Alfeno Varo, 35 - Alfianello (BS) - Italy;

**Sound power level (indoor unit / outdoor unit):** 63 / 67 dB(A);

**Refrigerant:** R32

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO<sub>2</sub>, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

### Cooling mode

**SEER:** 6.5

**Energy efficiency class:** A++

**Pdesignc:** 7.0 kW

Annual electricity consumption 377 kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

### Heating mode

**Climate type:** Average (-10°C) / Warmer (+2°C) / Colder (-22°C)

**SCOP:** 4,0/5,1/3,3

**Energy efficiency class:** A+/A+++/B

**Pdesignh:** 6,4/6,9/6,3 kW

The back up heating capacity for SCOP calculation: 0/0/0,8 kW.

Annual electricity consumption **2240/1894/4009** kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.